



OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025

Reviewed on 03/26/2025

1 Identification

· Product identifier

· Trade name: DuraSynth

· Product Code: ETS-70012

· Application of the substance / the mixture

Unpaved road dust control. Synthetic Fluid. Non-Chloride. Non-corrosive.

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Envirotech Services, LLC 910 54th Avenue Suite 230 Greeley, CO 80634 (970) 346-3900

· Information department: Product safety department

· Emergency telephone number: CHEMTREC: (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



Health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Proprietary Synthetic Fluid

· Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- · Components:

Proprietary Synthetic Fluid

100.0%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Generally this product does not irritate with inhalation.

If respiratory irritation occurs, consult a doctor.

· After skin contact:

Generally the product does not irritate the skin.

Wash with soap and water.

If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth out and then drink plenty of water.

Do not induce vomiting without medical advice.

If vomiting does occur, head should be kept low to prevent aspiration. Repeat fluid administration.

If irritation or discomfort occurs, consult a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(a)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Do not use water jet.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes, skin, and clothing.

- · Environmental precautions: Prevent from spreading (e.g. by damming-in or oil barriers).
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

None of the ingredients are listed.

· PAC-2

None of the ingredients are listed.

PAC-3:

None of the ingredients are listed.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(q)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

Components with	limit values that require monitoring at the workplace:	
Proprietary Synthetic Fluid		
TWA - ACGIH	Ceiling limit value: 5 mg/m³	
TWA - NIOSH REL	Short-term value: 10 mg/m³	
Ceiling limit value	5 mg/m³5	
TWA - OSHA P0	Ceiling limit value: 5 mg/m³	
TWA - OSHA Z-1	Ceiling limit value: 5 mg/m³	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink, smoke or sniff while working.

Avoid contact with eyes, skin, and clothing.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands: Not required.
- · Eye protection:



Goggles recommended during refilling.

· **Body protection:** Not required.

US

Safety Data Sheet OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 4)

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Liquid
Color:	Liquid Yellowish
Odor:	Mild
Odor threshold:	Not determined.
pH-value:	Mixture is non-soluble (in water).
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	285–452 °C (545–845.6 °F)
Flash point:	172 °C (341.6 °F)
Flammability:	Not applicable.
Auto igniting:	343 °C (649.4 °F)
Decomposition temperature:	Not determined.
lgnition temperature:	Not determined.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	0.0011 hPa (0 mm Hg)
Density at 20 °C (68 °F):	0.841-0.861 g/cm³ (7.01815-7.18505 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	<i>(er):</i> 2-6 (log Pow)
Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C (104 °F):	11.6 mm²/s
Solvent content:	
VOC content:	0.00 %

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 5)

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Reactive with oxidizing agents.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
	Proprieta	ry Synthet	ynthetic Fluid	
	Oral	LD50	>5,000 mg/kg (rat)	
	Dermal	LD50	>2,000 mg/kg (rabbit)	
	Inhalative	LC50/4 h	>5.53 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity: Proprietary Synthetic Fluid

EC50 >100 mg/kg /72 h (algae)

>100 mg/kg /48 h (daphnia magna (water flea))

LC50 >100 mg/l /96 h (fish)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 6)

- · **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Observe all federal, state, and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Non-Regulated Material	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Non-Regulated Material	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Non-Regulated Material	
· Packing group · DOT, ADR, IMDG, IATA	Non-Regulated Material	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	(II of Not applicable.	
· UN "Model Regulation":	Non-Regulated Material	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(a)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 7)

· Hazardous Air Pollutants

None of the ingredients are listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

TLV (Threshold Limit Value)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Proprietary Synthetic Fluid

Hazard statements

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that Envirotech Services, LLC beleives to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of Envirotech Services, LLC's control, Envirotech Services, LLC

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g)

Printing date 03/26/2025 Reviewed on 03/26/2025

Trade name: DuraSynth

(Contd. of page 8)

makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

- · Department issuing SDS: Lab
- · Contact: -
- · Date of preparation / last revision 03/26/2025 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Aspiration Hazard 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

US